





NUA-2467 TURMERIC



NUA-2451 WHITE




NUA-2452 SAND




NUA-2453 SANDSTONE



NUA-2466 KHAKI




NUA-2469 COCONUT HUSK



NUA-2468 GROUSE




NUA-2472 CHAMOIS




NUA-2473 COGNAC




NUA-2474 FIREFLY



NUA-2475 MERLOT



NUA-2471 ECLIPSE



NUA-2470 COFFEE BEAN



NUA-2476 SPRITE



NUA-2477 OCEAN



NUA-2459 NAVY



NUA-2457 EBONY

NUANCE™

Content

Vinyl | Urethane Topcoat

Backing

Hi-Loft²™

100% Polyester

Finishes

Napa Finish

Characteristics

Antibacterial

Antifungal

Mildew Resistant

No Heavy Metals

Formaldehyde Free

Performance

Superior Abrasion

CFFA 1, ASTM D-4157-02
100,000 cycles, Wyzenbeek #10 Cotton Duck

UV Stability

Xenotest: AATC TM 16-3/ CFFA-2 AI
1,000 Hours

Cold Crack -10°F

CFFA-6A



This fabric meets or exceeds these
ACT performance guidelines.

*Certification Marks owned by ACT®

Flame Retardancy*

California T.B. 117 - 2013

FMVSS 302

IMO FTP 2010 Code

MSC.307(88) Part 8, 3.1 & 3.2

NFPA 260 - Class I

UFAC - Class I & 2

*This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

Our vinyls, when tested with suitable component materials, may comply with California Technical Bulletin 133 and Boston Fire Code - Test BFD IX-1.

All Spradling International's vinyl and PU-coated fabrics contain flame retardant additives.

Specifics

Weight: 29 oz.

Width: 54 in.

Roll Size: 30 yd.

Applications

Automotive | RV

Education

Healthcare

Hospitality

Hotel | Motel | Casino

Restaurant

Theaters | Convention Centers

Marine

Interior

Exterior

Office

Residential

Interior

Exterior

NAPA™ Care and Cleaning Guide

STEP 1 Light soiling

Remove excess spill with a damp cloth. Use a solution of 10% household dish soap in warm water. Rub gently with a soft clean cloth, rinse with clean water, and dry.

STEP 2 Heavy soiling

Dampen a soft white cloth with a one-to-one (1:1) solution of warm water and an approved cleaner, such as Formula 409® or Fantastik®. Rub gently, rinse with a clean water-dampened cloth, and dry.

STEP 3 More difficult stains

Dampen a soft white cloth with a solution of 10% household bleach and warm water. Rub gently, rinse with a clean water-dampened cloth to remove bleach concentration, and dry.

*Do not use with alcohol-based cleaning agents.

This information is not a guarantee and does not relieve the user from the responsibility of the proper and safe use of the product and all cleaning agents. The use of certain agents can be harmful to the surface appearance and lifespan of vinyl. Spradling, its agents and assigns assume no responsibility resulting from the use of such cleaning agents to the vinyl.

Certain clothing and accessory dyes (such as those used on denim jeans) may migrate to lighter colors. This phenomenon is increased by humidity and temperature and is irreversible. Please check compatibility when using this product in combination with painted or varnished surfaces.

Formula 409® is a registered trademark of the Clorox Company.*

Fantastik® is a trademark of DowBrands, Inc.* Trademark of the Dow Chemical Co.*

Spradling International is not sponsored by, affiliated with, or endorsed by such trademark owners. Additionally, any use by Spradling International of any third-party trademark does not constitute any endorsement by Spradling International of such third party.

©2021 Spradling International, Inc.*

Due to the nature of numerous different computer and printer settings, the fabric & supply images displayed on this page may not represent the actual product in its entirety. All supplied fabric & supply images in their printed form are to be used for reference only and may not look exactly as shown.

En raison de la nature de nombreux paramètres d'ordinateur et d'imprimante différents, les images de tissu et de fournitures affichées sur cette page peuvent ne pas représenter le produit réel dans son intégralité. Toutes les images de tissu et de fournitures fournies sous leur forme imprimée doivent être utilisées à titre de référence uniquement et peuvent ne pas ressembler exactement à celles illustrées.



SPRADLING INTERNATIONAL, INC.®
Corporate Headquarters

200 CAHABA VALLEY PARKWAY
P.O. BOX 1668 | PELHAM, AL 35124

PHONE 800-333-0955

FAX 205-985-2354 | 205-985-9176

EMAIL orders@spradling.group

WWW.SPRADLING.GROUP

USA LOCATIONS

Pelham, Alabama
Fullerton, California
Grand Rapids, Michigan
Westampton, New Jersey
Maryville, Tennessee

INTERNATIONAL LOCATIONS

Europe (Spain | UK | Germany)
Mexico

Made exclusively for Spradling International, Inc.® by Proquinal S.A., Colombia, and Proquinal Costa Rica S.A. - An ISO 9001, ISO 14001, and TS 16949 company.

Some products may contain chemicals, identified by the State of California as a cause of cancer, birth defects or other reproductive harm at certain exposure levels. Under the California law known as "Prop 65," certain warnings to consumers in California are required where such products are sold. The presence of such chemicals in coated fabric products, even at extremely low concentrations, can lead to disputes over Prop 65 warning obligations that are very difficult to resolve. If your company intends to introduce Spradling vinyl products into commerce in California, Spradling recommends that you take steps to confirm whether the warning requirements of California's Prop 65 are applicable to the products in question and whether your company is complying with those warning requirements for the chemicals contained within these products.

11/2017